



PKPV15318DM5

183x1530x4.0mm+1.5mm IXPE, WEAR LAYER 0.5MM

SPC FLOOR TECHNICAL SHEET		
Product Specification	Test Standard	VERDICT
Composition		
Polyvinylchloride		26%
Calcium Carbonate		65%
Stabilizer		4%
Plasticizer		5%
General Info & Price		
Size		183x1530mm
Total thickness	EN 428	4,00 mm
Wear layer	EN 429	0,50 mm
IXPE		1.5mm
Unit N.W.(piece)		2.350 kgs
Total weight per Square meter	EN 430	8.4
Surface treatment		UV
click system		SPC Click
TECH DATA:		
Peeling strength of layers	EN 431	≥75N
Castor chair	EN 425	Pass
Fire resistance	EN 13501-1	Bfl -s1
Chemical resistance	EN 423	OK
Residual indentation	EN 433	≤0.10mm
Underfloor heating	EN 12524	0.096 W/(m.k)

Slip resistance	DIN 51130 EN 13893	DS $\geq$ 0.3
Dimensional stability	EN 434	$\leq$ 0.12%
Light fastness	ISO 105-B02	15
Toxicity	EN 71	Not toxic. Does not contain heavy metal and formaldehyde
Warranty		10 years
Abrasion Class	AC3 $\geq$ 2000-4000	13000

