

CODE	color
PK3G8080SC62	white

NAME OF SERIES OR ITEM NUMBER	netrual stone
LAST UPDATE	

Material (Material	fivth generation double loadng
FINISH (Acabado)	glossy
FINISH SURFACE	nano finish
PRODUCING TECHNIQUE	nano technical

TECHNICAL CHARACTERISTICS CARACTERISTICAS TECNICAS		PORCELAMIKA VALUES / VALORES	NORMA ISO 13006 REQUISITOS / REQUIREMENTS PAVIMENTOS	TEST METHOD AS PER IOS NORM TEST DE ACUERDO A
	LENGTH AND WIDTH DIMENSIONES (MM)	-0.01%~+0.04%	±0.5%	UNI EN ISO 10545-2
	STRAIGHTNESS OF SIDE RECTITUD LATERAL (MM)	- 0.45%~+1.73%	±0.5%	UNI EN ISO 10545-2
	RECTANGULAR SQUARENESS ORTOGONALIDAD (MM)	+0.01%~0.02%	±0.6%	UNI EN ISO 10545-2
	SURFACE FLATNESS PLANARIDAD (MM)	-0.01%~0.01%	±0.5%	UNI EN ISO 10545-2
	THICKNESS ESPESOR (MM)	10mm	±5%	UNI EN ISO 10545-2
	WATER ABSORPTION ABSORCION DE AGUA	0.02%	$E \leq 0.50 \%$	UNI EN ISO 10545-3
	BENDING RESISTANCE RESISTENCIA A LA FLEXION	50	$\geq 35\text{Mpa}$	UNI EN ISO 10545-4
	BREAKING STRENGTH FUERZA DE ROTURA	2282	$\geq 1300\text{N}$	UNI EN ISO 10545-4
	CHEMICAL RESISTANCE RESISTENCIA A PRODUCTOS QUIMICOS	GA	GB Para Esmaltados UB para Pulidos	UNI EN ISO 10545-14
	STAIN RESISTANCE RESISTENCIA A LA MANCHAS	6	$\geq \text{Grado } 3$	UNI EN ISO 10545-14
	ABRASION RESISTANCE (PEI) RESISTENCIA A LA ABRASION SUPERFICIAL (PEI)	102	Max. 175 mm3	UNI EN ISO 10545-7
	MOHS HARDNESS DUREZA SUPERFICIAL (ESCALA MOHS)	8	MOHS 1-10	UNI EN ISO 10545-7
	SHADE VARIATION CLASS VARIACION DE TONALIDAD	4	V1-V4	DIN 51094

PACKING INFORMATION

SIZE FORMATO	M2/BOX M2/CNT		BOX/PALLET CAJA/PALETA	M2/PALLET M2/PALETA	KG/BOX KG/CAJA	KG/PALLET KG/PALETA
800*800	1,92		32	61,44	42	1344

PICTURES

PKZM6060BT1	PKZM6060BT2	PKZM6060BT3
		

