

TECHNICAL SPECIFICATION

S.No.	Characteristics	IS 15622:2017 Group Bla	EN 14411:2016 Group Bla	Test method	SUNHEARRT VALUE	
A DIMENSION & SURFACE QUALITY						
I	Length & Width	± 0.1%	± 0.6%	ISO 10545-2	± 0.1%	
II	Thickness	± 5.0%	± 5.0%		± 4%	
III	Straightness of Side	± 0.1%	± 0.5 %		± 0.1%	
IV	Rectengularity	± 0.1%	± 0.5 %		± 0.1%	
V	Surface Flatness					
a	Center Curvature (%)	± 0.5 %	± 0.5 %		± 0.2 %	
b	Edge Curvature (%)	± 0.5 %	± 0.5 %		± 0.2 %	
c	Corner Warpage (%)	± 0.5 %	± 0.5 %		± 0.2 %	
VI	Surface Quality	Min. 95 % of tiles will be free from visible defects	Min. 95 % of tiles will be free from visible defects			Min. 98 % of tiles will be free from visible defects
B PHYSICAL PROPERTIES						
I	Water Absorption	<0.08% Ind Max 0.1%	<0.5% Ind Max 0.6%	ISO 10545-3	<0.05%	
II	Modulus of Rupture [N/mm ²]	Av 35, Individual 32 min.	Av 35, Individual 32 min.	ISO 10545-4	>45	
III	Breaking Strength in N	700 for < 7.5mm thickness 1300 for ≥ 7.5mm thickness	700 for< 7.5mm thickness 1300 for ≥ 7.5mm thickness	ISO 10545-4	>2000	
IV	Moisture Expansion in mm/m	0.02	0.06% / 0.6mm/m	ISO 10545-10	Nil	
V	Resistance to Abrasion of glazed tiles(Class I to V)	Depending on surface (As reported)	Depending on surface (As reported)	ISO 10545-7	Min. Class 3 for PGVT	
VI	Coefficient of linear thermal expansion from ambient temperature to 100.0 C	6 X 10 ⁻⁶ K ⁻¹	9 X 10 ⁻⁶ K ⁻¹ Max.	ISO 10545-8	6 X 10 ⁻⁶ K ⁻¹ max	
VII	Thermal Shock Resistance	10 Cycle Passed	10 Cycle Min.	ISO 10545-9	10 cycle min	
VIII	Crazing Resistance	4 Cycle	2 Cycle (@ 5 bar)	ISO 10545-11	4 cycle passed	
IX	Frost Resistance	100 Cycle	Required	ISO 10545-12	Passed	
X	Impact Resistance	0.55	0.55	ISO 10545-5	0.75	
XI	Bulk Density	2.2	Not a Requirement		2.2 gm/cc.min	
C CHEMICAL PROPERTIES						
I	Stain Resistance	Min. Class I	Min. Class 3	ISO 10545-14	Class 3	
II	Resistance to Household Chemicals	Class AA	Min. Class B	ISO 10545-13	Class A	

PACKING DETAILS

SIZE	PIECES / BOX	COVERAGE AREA / BOX		WEIGHT / BOX
120x278cm	1pc	34.00 sq. ft.	3.24 sq. meter	72 kg (approx)

Note: Color shown in catalog may vary with the original tile. Slight shade & size variation is an inherent property of Ceramic / Vitriified tiles. For Normal Glossy Class III, High Glossy Class II/Class III, Matt Class III/Class IV.